

# ATLAM OFFSHORE<sup>®</sup>

Load Lifting Solutions



**Cordas**  
**Cabos de Nylon**  
**Sisal**  
**Polietileno**  
**Polipropileno até 16"**



Circunferència Circunfer.	Diàmetro Diameter (Ø)		ACC 1 SISAL			ACC 2 NYLON			ACC 3 POLIETILENO POLYETHYLENE			ACC 4 POLIPROPILENO POLYPROPYLENE		
			Peso / Weight		Carga ruptura/ Breaking load Kg	Peso / Weight		Carga ruptura/ Breaking load Kg	Peso / Weight		Carga ruptura/ Breaking load Kg	Peso / Weight		Carga ruptura/ Breaking load Kg
			kg / m	220 m		kg / m	220 m		kg / m	220 m		kg / m	220 m	
pol. / in.	pol. / in.	mm												
3/8	1/8	3	-	-	-	0,006	1,3	185	0,005	1,1	105	0,004	0,9	140
1/2	5/32	4	-	-	-	0,011	2,4	320	0,008	1,8	200	0,007	1,5	270
5/8	3/16	5	-	-	-	0,016	3,5	500	0,013	2,9	280	0,010	2,2	390
3/4	1/4	6	0,025	5,5	270	0,024	5,3	750	0,018	4,0	400	0,017	3,7	550
1	5/16	8	0,045	9,9	483	0,042	9,2	1.350	0,033	7,3	700	0,030	6,6	960
1 1/4	3/8	10	0,070	15	635	0,065	14,0	2.080	0,049	11,0	1.090	0,045	10,0	1.425
1 1/2	1/2	12	0,10	22	955	0,094	21,0	3.000	0,072	16,0	1.540	0,065	14,0	2.030
1 3/4	9/16	14	0,14	31	1.285	0,128	28,0	4.100	0,095	21,0	2.090	0,090	20,0	2.790
2	5/8	16	0,18	40	1.800	0,166	37,0	5.300	0,128	28,0	2.800	0,115	25,0	3.500
2 1/4	3/4	18	0,23	51	2.140	0,210	46,0	6.700	0,161	35,0	3.500	0,148	33,0	4.450
2 1/2	13/16	20	0,28	62	2.850	0,260	57,0	8.300	0,200	44,0	4.300	0,180	40,0	5.370
2 3/4	7/8	22	0,34	75	3.400	0,315	69,0	10.000	0,243	53,0	5.100	0,220	48,0	6.500
3	15/16	24	0,40	88	4.070	0,375	82,0	12.000	0,295	65,0	6.100	0,260	57,0	7.600
3 1/4	1	26	0,47	103	4.660	0,440	97,0	14.000	0,340	75,0	7.100	0,305	67,0	8.900
3 1/2	1 1/8	28	0,55	121	5.330	0,510	112,0	15.800	0,393	86,0	8.000	0,355	78,0	10.100
3 3/4	1 3/16	30	0,63	139	6.070	0,585	129,0	17.800	0,460	101,0	9.200	0,405	89,0	11.500
4	1 1/4	32	0,72	158	6.860	0,665	146,0	20.000	0,525	115,0	10.400	0,460	101,0	12.800
4 1/2	1 7/16	36	0,91	200	8.700	0,840	185,0	24.800	0,660	145,0	13.000	0,585	129,0	16.100
5	1 5/8	40	1,12	246	10.420	1,040	229,0	30.000	0,785	173,0	15.600	0,720	158,0	19.400
5 1/2	1 3/4	44	1,36	299	12.700	1,260	277,0	35.800	0,950	209,0	18.800	0,880	194,0	23.400
6	1 7/8	48	1,61	354	14.740	1,500	330,0	42.000	1,150	253,0	22.400	1,040	229,0	27.200
6 1/2	2	52	1,89	416	17.280	1,750	385,0	48.800	1,340	295,0	26.200	1,220	268,0	31.500
7	2 3/16	56	2,20	484	19.820	2,030	446,0	56.000	1,575	346,0	30.200	1,420	312,0	36.000
7 1/2	2 3/8	60	2,52	554	22.600	2,330	512,0	63.800	1,800	396,0	34.200	1,630	359,0	41.200
8	2 1/2	64	2,87	631	25.700	2,650	583,0	72.000	2,030	447,0	38.600	1,850	407,0	46.800
9	2 7/8	72	3,63	799	32.700	3,360	739,0	90.000	2,590	570,0	48.500	2,340	515,0	58.600
10	3 5/32	80	4,48	986	38.700	4,150	913,0	110.000	3,210	706,0	58.400	2,900	638,0	72.000
11	3 1/2	88	5,42	1.192	46.800	5,020	1.104,0	131.000	3,870	851,0	70.300	3,510	772,0	85.400
12	3 3/4	96	6,45	1.419	53.500	5,980	1.316,0	154.000	4,610	1.014,0	84.500	4,170	917,0	102.000
13	4 1/8	104	7,60	1.666	62.500	7,018	1.544,0	179.000	5,410	1.190,0	99.000	4,870	1.071,0	119.000
14	4 3/8	112	8,80	1.932	72.000	8,140	1.791,0	205.000	6,270	1.379,0	114.000	5,640	1.241,0	137.000
15	4 3/4	120	10,1	2.218	83.000	9,345	2.056,0	232.000	7,200	1.584,0	130.000	6,480	1.426,0	156.000
16	5 1/16	128	11,5	2.532	93.000	10,636	2.340,0	260.000	8,200	1.802,0	147.000	7,400	1.622,0	176.000
17	5 3/8	136	12,9	2.848	104.000	12,0	2.640,0	290.000	9,200	2.034,0	164.000	8,300	1.831,0	197.000
18	5 11/16	144	14,5	3.193	117.000	13,477	2.960,0	320.000	10,400	2.280,0	183.000	9,300	2.052,0	219.000